

LAGRANGE COUNTY INDIANA

General Requirements for Driveway Approaches

A. Residential

1. Minimum width of driveway shall be 12'0"
2. Driveway surfaces shall be constructed using one of the following materials on County Right of Way
 - a. Processed gravel or limestone six (6) inches thick and compacted
 - b. Asphalt surface two (2) inches thick over four (4) inch compacted gravel subbase material
 - c. Portland cement concrete four (4) inches thick over well compacted subgrade
3. Culverts shall be minimum twelve (12) inches in diameter and shall be located in line with the existing road ditch
4. Culverts shall be backfilled with well compacted gravel or sand
5. County road side ditches shall be restored to original condition upon completion of driveway and culvert installation
6. Any excess excavated materials shall be disposed of off county right-of-way
7. All radius to driveway shall be a minimum of fifteen (15) feet

B. Commercial/Industrial Driveway Approaches

1. Minimum width shall be 22'0" with radius of 25' minimum
2. Commercial/industrial entrance surfaces shall be constructed of one of the following materials:
 - a. Crushed gravel or limestone minimum eight (8) inches thick and compacted
 - b. Asphalt surface two (2) inches thick over 6" compacted gravel subbase material
 - c. Portland cement concrete with wire mesh six (6) inches thick over well compacted subgrade

- d. Commercial or industrial driveways anticipating heavy truck load applicants should consult with the County Engineer prior to specifying pavement thickness
3. Culverts shall be minimum twelve (12) inch diameter and backfilled with compacted sand or gravel
4. County road side ditches shall be restored to original condition upon completion of driveway and culvert installation
5. Excess excavated materials shall be disposed of off county right-of-way

C. Farm Field Entrances

1. Minimum width 12'0" maximum width 24'0"
2. Minimum culvert size twelve (12) inch diameter backfilled with compacted sand or gravel
3. County road side ditches to be restored to original condition upon completion of driveway and culvert installation
4. Excess excavated material to be disposed of off county right-of-way